

CENELEC ENEC AGREEMENT

Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards

CERTIFICATE to Licence for ENEC Mark of Conformity



System No. 5, type testing with assurance of conformity
by production and market surveillance

Certificate ref. no.	IK-4287
Licence ref. no.	191624
Test report ref. no(s).	EFSH17122149-IE-02-L02
Name, address of licensee	ShenZhen Ruizi Light Electricity Technology Co.Ltd, Building 5, Yasen Innovative Industrial Park, No. 8, Chengxin RD, Baolong Indust. Town, Longgang District, Shenzhen 518116, CHINA
Name, address of factory	ShenZhen Ruizi Light Electricity Technology Co.Ltd, Building 5, Yasen Innovative Industrial Park, No. 8, Chengxin RD, Baolong Indust. Town, Longgang District, Shenzhen 518116, CHINA
European standards (safety)	EN 60598-1:15 EN 60598-2-1:89
Product	LED Tri-proof Light
Trade mark	---
Product identification	see page 2
Ratings, characteristics	100-240V~, 50/60Hz, Max.80W Class I
Degree of protection	IP65; Non-replaceable LED module
Classification	Class I
Limitations	---
Remarks	---

Production surveillance according to CENELEC harmonized procedure and ENEC requirements. This document is issued by Electrosuisse as National Certification Body within the ENEC scheme. This document is valid until 2021-02-21.
This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

**Electrosuisse
Swiss Certification Body**

Jürg Rellstab
Product Certification



CENELEC ENEC AGREEMENT

Agreement on the use of a commonly agreed Mark of Conformity for certain electrical equipment complying with European Standards

CERTIFICATE to Licence for ENEC Mark of Conformity

Type designation:

T21CX-XX-XX-XXXXX-XXX
L07CX-XX-XX-XXXXX-XXX
T60AX-XX-XX-XXXXX-XXX
T07CX-XX-XX-XXXXX-XXX
T66AX-XX-XX-XXXXX-XXX

- The first X for T60 series can be P(PC) or M(PMMA) and for other series can be P(PC);
- the second X can be C(standard) or L(linkable);
- the third X can be C(common), D(DALI), Z(1-10V) or M(Sensor);
- the 4th and 5th X can be 20(20W), 25(25W), 30(30W), 35(35W), 36(36W), 40(40W), 48(48W), 50(50W), 54(54W), 60(60W), 80(80W);
- the 6th to 9th X can be 0600(600mm), 0900(900mm), 1200(1200mm) or 1500(1500mm);
- the 10th X can be K(frosted), C(clear);
- the 11th and 12th X can be 27(2700K), 30(3000K), 40(4000K), 50(5000K), 65(6500K);
- the 13th X can be L(normal efficiency), M(medium efficiency), H(high efficiency) or G(super efficiency).