



ABOUT US

WELCOME TO LEDPROFZ.

LEDPROFZ is the expert in LEDlighting for the industrial and commercial market. We supply innovative and proven lighting technologies for the professional market. We exclusively imports Ervan LED fixtures. Continuous innovation, consistently high quality production,and reliable quality assurance are the basic definition of ERVAN luminaires.

Thanks to large-scale imports and a business model with very low costs, our customers benefit from the best price level in the market.

LED TRI-PROOF LIGHT

- PLUS VERSION HIGHPOWER TRI-PROOF--T21
- EXCITE TRI-PROOF LUMINAIRE---T07
- PRO VERSION TRI-PROOF--T09
- BASIC VERSION TRI-PROOF--T66

EMERGENCY

- PLUG & PLAY EMERGENCY MODULE--E02

HIGH BAY

- LOW GLARE LED HIGH BAY--H29
- EASY CLEAN HIGH BAY--H09

FLOOD LIGHT

- FLOOD LIGHT--EFL12


LED PANEL

- BACK LIT PANEL--P30
- SIDE-LIT LED PANEL--P01
- LED DOWNLIGHT--R01
- LED CCT DIM DOWNLIGHT--R05

LED TUBE

- T8 TUBE--L05G-H
- Integrated T5 TUBE-T5-AE

LED TRI-PROOF LIGHT





IK08 IP65



Simple connection

push-on connector
5*1.5mm²; 5*2.5mm²



Built-in Sensor


PLUS VERSION-HIGHPOWER TRI-PROOF-T21




T21 is a robust and powerful luminaire designed for multiple application such as Warehouse, factory, logistics center, indoor sports hall, Swimming pool etc..

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
1200mm	40W	6400LM	160lm/w	80	4000K	3
1500mm	60W	9600LM	160lm/w	80	4000K	3
1500mm	80W	12800LM	160lm/w	80	4000K	3
1500mm	100W	16000LM	160lm/w	80	4000K	3
1500mm	120W	19200LM	160lm/w	80	4000K	3
1500mm	150W	24000LM	160lm/w	80	4000K	3

Input: AC220~240V 50/60Hz
Wiring: 5 wires through available
Operation Temp: -20~40°C
Function: 1~10V DIM | DALI | SENSOR | Emergency
Flicker: Flicker free

Material: PC+Aluminum
Installation: Ceiling mounted | Suspension
Protection: IP65 | IK08
Terminal: 5x1.5mm²/5x2.5mm² push






EXCITE TRI-PROOF LUMINAIRE-T07

T07C is versatile and robust luminaire which makes it suitable in a wide range of industrial and commercial applications. The luminaire is supplied with V0-rated polycarbonate diffuser and powder painted aluminium heat sink, it can be also supplied with integrated sensor and intelligent emergency kit.

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
600mm	20W	3200LM	160lm/w	80	4000K	3
1200mm	40W	6400LM	160lm/w	80	4000K	3
1500mm	50W	8000LM	160lm/w	80	4000K	3
1500mm	65W	10400LM	160lm/w	80	4000K	3

Input: AC220~240V 50/60Hz
Wiring: 3 wires through available
Operation Temp: -20~40°C
Function: 1~10V DIM | Motion Sensor | Emergency | DALI
Flicker: Flicker free

Material: PC+Aluminum
Installation: Ceiling mounted | Suspension
Protection: IP65 | IK08
Terminal: 3x1.5mm² | 3x2.5mm² push






Tool Free and Fast Installation
Rotating End Cap

Simple connection
push-on connector
5*1.5mm²; 5*2.5mm²



V0 Opal Cover



PRO VERSION TRI-PROOF-T09



T09 is a professional but different industry Damp Proof Luminaire which brings you impressive values for application of 3-8m. Cables are Tool Free and fast mounting on either sides with Rotating End cap and Push on Connector.

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
1200mm	40W	6400LM	160lm/w	80	4000K	3
1500mm	50W	8000LM	160lm/w	80	4000K	3
1500mm	63W	10080LM	160lm/w	80	4000K	3

Input: AC220~240V 50/60Hz
Wiring: 5 wires through available
Operation Temp: -20~40°C
Function: 1~10V DIM | Motion Sensor | Emergency | DALI
Flicker: Flicker free

Material: PC
Installation: Ceiling mounted | Suspension | Wire cable
Protection: IP65 | IK08
Terminal: 5x1.5mm² | 5x2.5mm² push

CCT: Color temperature adjustable available





Tool Free and Fast Installation
Rotating End Cap

Simple connection
push-on connector
3*1.5mm²; 3*2.5mm²



V0 Opal Cover




BASIC VERSION TRI-PROOF-T66

T66 has the most uniform illumination and wide lighting distribution thanks to the ultra slim design, it's recommended as an ideal solution to a lot of applications such as parking lots, factory,. low-racked warehouses...

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
600mm	20W	3200LM	160lm/w	80	4000K	3
1200mm	30W	4800LM	160lm/w	80	4000K	3
1500mm	40W	6400LM	160lm/w	80	4000K	3

Input: AC220~240V 50/60Hz
Wiring: 3 wires through available
Operation Temp: -20~40°C
Function: 1~10V DIM | DALI

Material: PC
Installation: Ceiling mounted | Suspension
Protection: IP65 | IK08
Terminal: 3x1.5mm² | 3x2.5mm² push
CCT: Color temperature adjustable available



EMERGENCY





3W



3H EMERGENCY



LITHIUM BATTERY



2 YEAR WARRANTY



BATTERY CHANGEABLE




AUTO-TEST

PLUG & PLAY EMERGENCY MODULE-E02


Maintenance and warranty is always a problem for emergency solution, especially for internal emergency solution. Now we have ERVAN smart IP65 plug and play emergency module which is suitable perfectly for all industrial product with easy installation, and smart design with auto-test function and battery changeable function to make sure lowest maintenance costs.


Dimmension	Power	Lumen Output	Efficiency	CRI	CCT	Current Capacity
Ø86*57mm	3W	390LM	130lm/w	>80	4000K	2200mAh 7.4V
AC220-240V Storage Temperature: -40~+85°C Operating Temperature: -20~+40°C						
Protection : IP65 IK06						

BATTERY CHANGEABLE



LED HIGH BAY





GLOBAL PATENT (No. 004670651-0001)

Honeycomb Design
UGR<22
Power Adjustable 100-120-150-200W




LOW GLARE LED HIGH BAY-H29

With global patent honeycomb design, ERVAN UFO can offer real low glare lighting output even at big power 200w according to precise optic control technology, best options for industrial applications.

Size	Wattage	Lumen	Efficiency	Beam Angle	CRI	CCT	SDCM	UGR
Ø280mm	100W	15000	150lm/w	75°	80	4000K	3	22
Ø280mm	150W	22500	150lm/w	75°	80	4000K	3	22
Ø360mm	200W	30000	150lm/w	75°	80	4000K	3	22

Input: AC100~240V 50/60Hz
Operation Temp: -30~50°C
Function: 1~10V DIM | DALI | SENSOR | Emergency
Flicker: Flicker free


Material: Aluminum
Installation: Ceiling mounted | Suspension
Protection: IP65 | IK08





GLOBAL PATENT (No. 004670651-0001)

Honeycomb Design
UGR<22
Power Adjustable 100-120-150-200W




LOW GLARE LED HIGH BAY-H09

With global patent honeycomb design, ERVAN UFO can offer real low glare lighting output even at big power 200w according to precise optic control technology, best options for industrial applications.

Size	Wattage	Lumen	Efficiency	Beam Angle	CRI	CCT	SDCM	UGR
Ø280mm	100W	14000	140lm/w	80°	80	4000K	3	22
Ø280mm	150W	21000	140lm/w	80°	80	4000K	3	22
Ø360mm	200W	28000	140lm/w	80°	80	4000K	3	22

Input: AC100~240V 50/60Hz
Operation Temp: -30~50°C
Function: 1~10V DIM | DALI | SENSOR | Emergency
Flicker: Flicker free

Material: Aluminum
Installation: Ceiling mounted | Suspension
Protection: IP65 | IK10



FLOOD LIGHT





FLOOD LIGHT-EFL12

ERVAN Floodlight product is good option for both indoor and outdoor applications with wide power range from 10~300W and stable IP65 water-proof function, customized robust die-casting aluminium structure ensures strong protection at harsh environment. Multiple light angles meets multile application requirement.

Size	Wattage	Lumen	Efficiency	CRI	CCT
127*98*43mm	10	1400	140lm/w	80	4000K
148*119*39mm	20	2800	140lm/w	80	4000K
202*162*42mm	30	4200	140lm/w	80	4000K
247*201*41mm	50	7000	140lm/w	80	4000K
302*242*50mm	100	14000	140lm/w	80	4000K
359*277*56mm	150	21000	140lm/w	80	4000K
412*322*58mm	200	28000	140lm/w	80	4000K
486*358*65mm	250	35000	140lm/w	80	4000K
486*358*65mm	300	42000	140lm/w	80	4000K

Input: AC100~240V 50/60Hz
Operation Temp: -30~50°C
Function: 1~10V DIM | DALI | SENSOR
Flicker: Flicker free

Material: Glass+Aluminum
Installation: Wall mounted | Ground mounted
Protection: IP65


Beam angle: 15/30/45/60/90/120/t2m/t3m



LED PANEL



ERVAN®



180° wide beam lens
Uniform lighting

Prismatic diffuser
UGR<19

Seamless molding process



BACK LIT PANEL-P30

ERVAN Backlit panel provides excellent visual comfort with micro prismatic diffuser and SDCM 3 color uniformity, tunable white function with circadian rhythms LEDs which is good HCL solution for applications such as schools, offices and supermarket..


Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM	UGR
595*595*35mm	36W	4320LM	120lm/w	>80	4000K	3	19
1195*295*35mm	36W	4320LM	120lm/w	>80	4000K	3	19
1195*595*35mm	72W	8640LM	120lm/w	>80	4000K	3	19
620*620*35mm	36W	4320LM	120lm/w	>80	4000K	3	19

Input: AC220~240V 50/60Hz
Wiring: Loop in & loop out available
Operation Temp: -20~40°C
Function: 1~10V DIM | DALI
Flicker: Flicker free available
Driver: Power adjustable available

Material: Aluminum
Installation: Ceiling mounted; Suspension
Protection: IP20/IK06

CCT: Tunable white 2700-6500k available





SIDE-LIT LED PANEL -P01

ERVAN Sidelit light panel is designed with 11mm slim and robust structure which is an ideal solution to retrofit the traditional grille fixture into more comfortable and eyes friendly lighting result for applications such as classroom, office and supermarket..

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM	UGR
1195*595*11mm	60W	7200LM	120lm/w	80	4000K	3	19
620*620*11mm	36W	4320LM	120lm/w	80	4000K	3	19
595*595*11mm	36W	4320LM	120lm/w	80	4000K	3	19
1195*295*11mm	36W	4320LM	120lm/w	80	4000K	3	19
595*295*11mm	22W	2640LM	120lm/w	80	4000K	3	19
295*295*11mm	15W	1800LM	120lm/w	80	4000K	3	19

Input: AC220~240V 50/60Hz
Wiring: Loop in & loop out available
Operation Temp: -20~40°C
Function: 1~10V DIM | DALI
Flicker: Flicker free available
Driver: Power adjustable available

Material: Aluminum
Installation: Ceiling mounted; Suspension
Protection: IP20/IK06


CCT: Tunable white 2700-6500k available



Seamless White frame

PMMA LGP

Prismatic diffuser
UGR<19



LED DOWNLIHT--R01

LED DOWNLIGHT use indirect lighting for downy light and visually comfortable.

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
Φ180mm	10W	7200LM	85lm/w	80	4000K	3
Φ240mm	15W	1275LM	85lm/w	80	4000K	3
Φ300mm	22W	1870LM	85lm/w	80	4000K	3

Comfortable light


Aluminum frame

PMMA LIGHT guide

Input: AC220~240V 50/60Hz
Operation Temp: -20~40°C
Flicker: Flicker free available

Driver: Power adjustable available
Material: Aluminum+PC
Installation: Ceiling mounted; Suspension
Protection: IP20/IK06






LED DOWNLIGHT-R05


R05 frameless recessed downlight suit for different cut-out with adjustable rail. With color-controlled, power-adjusted, it greatly reduce the cost of electrical installation.

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
Φ120mm	10W	1100LM	110lm/w	80	4000K	3
Φ170mm	15W	1650LM	110lm/w	80	4000K	3
Φ225mm	20W	2200LM	110lm/w	80	4000K	3



Input: AC220~240V 50/60Hz
Operation Temp: -20~40°C
Flicker: Flicker free available

Driver: Power adjustable available
Material: Aluminum+PC
Installation: Ceiling mounted; Suspension
Protection: IP20/IK06
CCT: Tunable white 2700-6500k available





Adjustable rail for different cut-out
Φ75 - 210 mm

Seamless White frame

CCT& Power adjustable

LED TUBE






T8 TUBE -L05G-H

ERVAN LED T8 tube is unique design, great quality with ultra high efficiency and lighting uniformity. SDCM<3, flicker free and customized LED internal driver which could meet the latest international safety directive, reliable option for your project.

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
600mm	9W	1620LM	180lm/w	>80	4000K	3
1200mm	12W	2160LM	180lm/w	>80	4000K	3
1500mm	18W	3240LM	180lm/w	>80	4000K	3
1500mm	24W	4320LM	180lm/w	>80	4000K	3

Input: AC220-240V 50/60Hz
Operation Temp: -20~40°C
Flicker: Flicker free available

Material: PC+Aluminum
Installation: Retrofit
Protection: IP20 | IK06



V0 PC Cover

Fixture Integrated

Easy connectable




INTEGRATED TUBE-T5-AE

Luminaire with integrated T5 LED Tube and independent power supply can be linked to a light line

Size	Wattage	Lumen	Efficiency	CRI	CCT	SDCM
600mm	11W	1650LM	150lm/w	>80	4000K	3
1200mm	20W	3000LM	150lm/w	>80	4000K	3
1500mm	24W	3600LM	150lm/w	>80	4000K	3

Input: AC220~240V 50/60Hz
Operation Temp: -20~40°C
Flicker: Flicker free available

Driver: Power adjustable available
Material: Aluminum+PC
Installation: Ceiling mounted; Suspension
Protection: IP20/IK06





Randweg-Zuid 36 6021 PT Cranendonck

Tel (+31) 040 - 369 06 95

Mail: info@LEDProfz.nl

www.ledprofz.nl